




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>5</sup> : <b>A61B 17/56, A61L 25/00</b> <b>// A61F 2/46</b>		<b>A1</b>	(11) International Publication Number: <b>WO 90/13264</b>
			(43) International Publication Date: 15 November 1990 (15.11.90)
(21) International Application Number: <b>PCT/SE90/00018</b>		(74) Agent: <b>WILLQUIST, Bo; Pats. Willquist Patent AB, S:t Larsgatan 29, S-582 24 Linköping (SE).</b>	
(22) International Filing Date: <b>11 January 1990 (11.01.90)</b>			
(30) Priority data: <b>8901599-4</b> <b>3 May 1989 (03.05.89)</b> <b>SE</b>		(81) Designated States: <b>AT</b> (European patent), <b>AU</b> , <b>BE</b> (European patent), <b>CA</b> , <b>CH</b> (European patent), <b>DE</b> (European patent), <b>DK</b> , <b>DK</b> (European patent), <b>ES</b> (European patent), <b>FI</b> , <b>FR</b> (European patent), <b>GB</b> (European patent), <b>IT</b> (European patent), <b>JP</b> , <b>KR</b> , <b>LU</b> (European patent), <b>NL</b> (European patent), <b>NO</b> , <b>SE</b> (European patent), <b>SU</b> , <b>US</b> .	
(71) Applicant (for all designated States except US): <b>SURGITEC AB [SE/SE]; Breviksvägen 3, S-311 45 Falkenberg (SE).</b>		Published With international search report. In English translation (filed in Swedish).	
(72) Inventors; and (75) Inventors/Applicants (for US only) : <b>SMEDS, Staffan [SE/SE]; Lövgatan 12, S-582 45 Linköping (SE). JONSSON, Sören [SE/SE]; Rönnhagsvägen 38, S-582 70 Linköping (SE). THORLING, Jan [SE/SE]; Lilla Hälla 4242, S-791 91 Falun (SE). NILSSON, Thomas [SE/SE]; Breviksvägen 3, S-311 45 Falkenberg (SE).</b>			

(54) Title: **DEVICE FOR PREPARING BONE CEMENT**

## (57) Abstract

The present invention relates to an arrangement for the manufacture of bone cement by mixing together its constituent components comprising a mixing cylinder (1) in the form of a tube with a bottom (2) and a lid (3) and inside the mixing cylinder an axially movable agitator (4). The agitator consists of a piston-like agitator disc (4a), which is perforated by channels (4a1), through which the components of the bone cement are caused to flow during the mixing procedure and an agitator rod (4b) resembling a piston rod operatively connected to the agitator disc (4a) and supported in the lid (3) in such a way that it is free to slide. The invention is characterized in that the agitator rod (4b) has an axial channel (4b1), which is closed off at the agitator disc (4a) in such a way that it is capable of being opened. The bottom (2) is so arranged, under the effect of an axial force, as to be displaced like a piston axially in the direction of the lid (3), in conjunction with which the bone cement flows out through the channel (4b1) after it has been opened.



### DESIGNATIONS OF "DE"

Until further notice, any designation of "DE" in any international application whose international filing date is prior to October 3, 1990, shall have effect in the territory of the Federal Republic of Germany with the exception of the territory of the former German Democratic Republic.

#### *FOR THE PURPOSES OF INFORMATION ONLY*

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MC	Monaco
AU	Australia	FI	Finland	MG	Madagascar
BB	Barbados	FR	France	ML	Mali
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GR	Greece	NL	Netherlands
BJ	Benin	HU	Hungary	NO	Norway
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	SD	Sudan
CF	Central African Republic	KP	Democratic People's Republic of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SN	Senegal
CH	Switzerland	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
DE	Germany, Federal Republic of	LU	Luxembourg	TC	Togo
DK	Denmark			US	United States of America

Device for preparing bone cement.

The present invention relates to an arrangement for the manufacture of bone cement by mixing together its constituent components comprising a mixing cylinder in the form of a tube with a bottom and a lid and inside the mixing cylinder an axially movable agitator in the form of a piston-like agitator disc, which is perforated by channels, through which the components of the bone cement are caused to flow during the mixing procedure and an agitator rod resembling a piston rod operatively connected to the agitator disc and supported in the lid in such a way that it is free to slide.

Bone cement is used in hip-joint operations, for example. When manufacturing bone cement, for which purpose a component in the form of a powder and a liquid component require to be mixed, it is important that the mixture should be as homogeneous as possible, and that gases which occur during the mixing procedure are removed to the greatest extent possible. Any lack of homogeneity and gas inclusions have the effect of reducing the strength of the bone cement, which can result in a shorter service life for the implanted prosthesis. Furthermore, the gases which occur during manufacture are unhealthy, for which reason steps must be taken to ensure that they do not escape into the operating theatre.

The object of the present invention is to make available a preparation arrangement for bone cement, which is intended to be disposable and capable of being manufactured efficiently and at a low cost, and which also contributes to meeting the requirements stipulated above in respect of the prepared bone cement.

This object is met in that the agitator rod has an axial

**SUBSTITUTE SHEET**

channel, which is closed off at the agitator disc in such a way that it is capable of being opened, in that the bottom is executed with a device projecting towards the agitator disc arranged in such a way, when mixing is complete, as to penetrate the membrane at that time, and in that the bottom is so arranged, under the effect of an axial force, as to be displaced like a piston axially in the direction of the lid, in conjunction with which the bone cement flows out through the channel in the agitator rod.

Additional advantages of the invention can be appreciated from the accompanying dependent claims and from the following description with reference to the accompanying drawing, in which Figs. 1a and 1b illustrate schematically in longitudinal section a mixing cylinder with a bottom and an agitator supported in a lid in such a way that it is free to slide, in accordance with a first embodiment of the preparation arrangement in accordance with the invention. Fig. 1c illustrates an agitator disc in accordance with the invention viewed from below. Fig. 2 is a longitudinal section through an arrangement in accordance with the aforementioned first embodiment, and Fig. 3 illustrates in detail the penetration of a sealing membrane. Fig. 4 illustrates how the aforementioned first embodiment of the preparation arrangement in accordance with the present invention is used as a bone cement syringe. Fig. 5 is a longitudinal section through a second embodiment of the preparation arrangement in accordance with the invention.

The designation 1 is used in the drawing for a mixing cylinder, and 2 for a bottom which is inserted in a sealing fashion into one end of the mixing cylinder 1. The mixing cylinder 1 is preferably made from a transparent material, and the bottom 2, which, for

reasons which will become clear later, is made from a rubber-like elastic material, is executed with a projecting stud 2a facing towards the inside of the cylinder and has an annular flange-like projection 2b which engages in a corresponding groove 1a in the inner wall of the mixing cylinder 1.

The preparation arrangement in accordance with the invention also includes a lid 3 with an agitator 4 capable of axial movement therein. This comprises a piston-like agitator disc 4a and an agitator rod 4b supported in the lid 3 in such a way that it is free to slide. The lid is sealed against the inner wall of the mixing cylinder 1 and against the agitator rod 4b by means of 'O'-rings 5 and 6. The lid 3 also exhibits an evacuation channel 3a, which, via a line 7, is capable of connection to a vacuum source (not shown here), and which, when the lid 3 is fitted, discharges into the internal space of the mixing cylinder.

The agitator disc 4a is perforated by channels 4a1, through which the bone cement components are caused to flow during agitation in order to make this as effective as possible. The agitator rod 4b exhibits in accordance with the invention an axial channel 4b1, which is closed off at the end of the rod 4b which is attached to the agitator disc 4a. The closure consists of a penetrable membrane 4c. This has fractural impressions 4c1, which are illustrated in Fig. 1c.

A dot screen and the designation 8 are used in Fig. 1a to indicate a powder, and the designation 9 and a pattern of dashes to indicate a liquid, which are the components of the bone cement and have been introduced into the mixing cylinder 1 via the opening which is intended to be closed off by means of the lid 3. In the interests of

clarity, these components are omitted from the other Figures.

5 The mixing procedure itself is illustrated in Fig. 2. With the help of the agitator rod 4b, the agitator disc 4a is caused to move up and down inside the mixing cylinder 1. This movement is indicated by means of a bidirectional arrow 10 in Fig. 2. Bidirectional arrows 11 are also used in the same Figure to illustrate how the components 8, 9 are caused in this way to flow through the channels 4a1 and through a space between the agitator disc 4a and the internal wall of the cylinder 1. Since the cylinder wall is transparent, a person skilled in the art can easily decide when the preparation of the bone cement is complete.

15 Once it has been established that the preparation is complete, the agitator 4 is moved downwards with a deliberate movement, which in Fig. 3 is illustrated by a downward-facing arrow 12, so that the agitator disc 4a comes into contact with the bottom 2. This results in penetration of the membrane 4c by the stud 2a, causing the membrane to rupture along the fractural impressions 4c1, which is illustrated by arrows 13 in Fig. 3. The agitator is then pulled to the position illustrated in Fig. 4. The channel 4b1 inside the agitator rod 4b now communicates with the space inside the mixing cylinder 1 in which the prepared bone cement is present.

20 The preparation arrangement in accordance with the invention is now placed inside a syringe mechanism of the kind which is customarily used for the extrusion of sealing compound or similar in the form of a bead. This mechanism is indicated in Fig. 4 on the one hand as a holder part 14 marked as broken lines, in which the mixing cylinder 1 with its bottom 2, lid 3 and agitator

25

30

35

4 are placed, and on the other hand as a compression piston 15 with an associated compression rod 16.

When the compression piston 15 is caused to press against the bottom 2, which is illustrated by an upward-facing arrow 17, and when the compressive force has reached a sufficiently high level, the annular flange-like projection 2b will, as compression takes place, be forced out of the groove 1a and will function as a seal against the inner wall of the mixing cylinder 1. The bottom 2 now acts as a piston and forces the bone cement through the penetrated membrane 4c and via the channel 4b1 to the outside for its intended use, as shown by an arrow 18. The same reference designations are used in Fig. 5 in respect of details with the same function as, or with an analogous function to the corresponding details in the earlier Figures. This Figure illustrates the alternative embodiment of the preparation arrangement in the state in which it is supplied for use. The mixing cylinder 1 and lid 3 are manufactured in a single piece in this case, and the lid part 3, like the embodiment described above, has an evacuation channel 3a and a seal 5 against the agitator rod 4b. The bottom 2 in this case is formed as an outwardly open cup with annular flange-like seals 2b in contact with the inner wall of the mixing cylinder 1.

Unlike the embodiment of an arrangement in accordance with the invention for the manufacture of bone cement described above, the embodiment in accordance with Fig. 5 has a funnel 19 removably attached to the outer end of the agitator rod 4b and a rod 20 introduced into the axial channel 4b1 of the agitator rod 4b, together with a tubular holder 21 into which the mixing cylinder 1 is introduced. The narrow opening of the funnel 19 is in close contact with the agitator rod 4b, and its purpose is to facilitate the introduction of the bone cement

components into the mixing cylinder 1, for which purpose the rod 20 must have been pulled from the channel 4b1. The rod 20 is of a length such that, when introduced fully into the channel 4b1, it reaches into the vicinity of the agitator disc 4a and is in this area executed with a seal 20a in contact with the inner wall of the channel 4b. The rod 20 with the seal 20a corresponds in its function to the membrane 4c1 described above. At its opposite end the rod 20 is executed with a draw ring 20b or similar. The mixing cylinder 1 and the piston 2 are fixed relative to the holder 21 by means of a removable cotter pin 22.

The preparation arrangement in accordance with Fig. 5 is used as follows: The rod 20 is first removed so that the bone cement components can be introduced into the mixing cylinder 1 via the channel 4b1. The funnel 19 is then removed, and the rod 20 is introduced into the channel 4b1. The bone cement components are now mixed together, as previously described in conjunction with Figure 2, when any gases which occur are removed via the channel 3a. During the mixing procedure the arrangement is placed in the holder 21. Once the mixing procedure is complete, the cotter pin 22 is withdrawn from its position, thereby enabling the preparation arrangement to be removed freely from its holder 21 and placed in the syringe mechanism in the manner explained in conjunction with Figure 4. Once the cotter pin 22 has been removed, the piston 2 can be displaced axially under the effect of the compression piston 15. Once the rod 20 has been removed from the channel 4b1, bone cement can be forced out through it for the intended use.

Patent Claims

1. Arrangement for the manufacture of bone cement by mixing together its constituent components comprising a mixing cylinder (1) in the form of a tube with a bottom (2) and a lid (3) and inside the mixing cylinder an axially movable agitator (4) in the form of a piston-like agitator disc (4a), which is perforated by channels (4a1), through which the components of the bone cement are caused to flow during the mixing procedure and an agitator rod (4b) resembling a piston rod operatively connected to the agitator disc (4a) and supported in the lid (3) in such a way that it is free to slide, characterized in that the agitator rod (4b) exhibits an axial channel (4b1), which is closed off at the agitator disc (4a), and in that the bottom (2) is so arranged, under the effect of an axial force, as to be displaced like a piston axially in the direction of the lid (3), in conjunction with which the bone cement flows out through the channel (4b1) after it has been opened.

2. Arrangement in accordance with Patent Claim 1, characterized in that the closure of the channel (4b1) is achieved with a rod capable of being introduced into the channel, which rod is executed at one end with a seal, which, when in its introduced position in the area around the agitator disc (4a), is in contact with the inner wall of the channel (4b1).

3. Arrangement in accordance with Patent Claim 1, characterized in that the channel (4b1) is closed off by means of a penetrable membrane (4c), in that the bottom (2) is executed with a device (2b)

projecting towards the agitator disc so arranged, when mixing is complete, as to penetrate the membrane (4c) when the agitator (4) is displaced axially against the bottom (2).

5

4. Arrangement in accordance with Patent Claim 1, characterized in that the lid (3) exhibits an evacuation channel (3a) capable of connection to a vacuum source and so executed that, when the lid (3) is fitted, it discharges into the internal space of the mixing cylinder (1).

10

5. Arrangement in accordance with Patent Claim 1, characterized in that the mixing cylinder (1) is transparent.

15

6. Arrangement in accordance with Patent Claim 2, characterized in that the agitator rod (4b) exhibits at its outer end a funnel intended to facilitate the filling of the components via the channel (4b1).

20






FIG 3




FIG 4






FIG 5



# INTERNATIONAL SEARCH REPORT

International Application No PCT/SE 90/00018

<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (if several classification symbols apply, indicate all) <sup>6</sup>		
According to International Patent Classification (IPC) or to both National Classification and IPC		
IPC5: A 61 B 17/56, A 61 L 25/00 // A 61 F 2/46		
<b>II. FIELDS SEARCHED</b>		
Minimum Documentation Searched <sup>7</sup>		
Classification System	Classification Symbols	
IPC5	A 61B; A 61L; A 61M; A 61F; A 61J; B 65D; B 01F; A 61C	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in Fields Searched <sup>8</sup>		
SE,DK,FI,NO classes as above		
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT<sup>9</sup></b>		
Category *	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>
A	WO, A1, 8803811 (LABORATORIUM FUR EXPERIMENTELLE CHIRURGIE, FORSCHUNGSINSTITUT) 2 June 1988, see abstract; figures 2-6; claims 1-11 --	1-6
A	WO, A1, 8705492 (DRAENERT) 24 September 1987, see abstract; figures 1-8 --	1-6
A	FR, A1, 2286657 (INSTITUT DE SEROTHERAPIE DE TOULOUSE) 30 April 1976, see figures 1-5 see claim --	1-6
A	DK, B, 123745 (PRODUCTS RESEARCH & CHEMICAL CORP.) 31 July 1972, see figures 1-7; claims 1-2 --	1-6
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>* Special categories of cited documents:<sup>10</sup></p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&amp;" document member of the same patent family</p> </div> </div>		
<b>IV. CERTIFICATION</b>		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
11th May 1990	1990 -05- 15	
International Searching Authority	Signature of Authorized Officer	
SWEDISH PATENT OFFICE	Hans Peterson 	

Form PCT/ISA/210 (second sheet) (January 1985)

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No
A	SE, B, 447785 (MIT AB) 15 December 1986, see abstract; figures 1-2; claims 1-10 -- -----	

Form PCT/ISA/210 (extra sheet) (January 1985)

# Best Available Copy

## ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.PCT/SE 90/00018

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the Swedish Patent Office EDP file on 90-05-07  
The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A1- 8803811	88-06-02	EP-A- 0290433	88-11-17
WO-A1- 8705492	87-09-24	DE-A- 3609672	87-09-24
		EP-A- 0261182	88-03-30
		EP-A- 0262185	88-04-06
		JP-T- 63502882	88-10-27
		JP-T- 63502883	88-10-27
		WO-A- 87/05491	87-09-24
FR-A1- 2286657	76-04-30	NONE	
DK-B- 123745	72-07-31	NONE	
SE-B- 447785	86-12-15	DE-A- 3640279	87-06-25
		US-A- 4758096	88-07-19